



HE53 Halogen Moisture Analyzer

Reliable Results

Simple Operation

Affordable Quality

Moisture Matters

Quick and Easy Analysis



Reliable, Easy and Affordable A Sound Investment in Quality

The HE53 halogen moisture analyzer is a reliable and cost-effective solution for determining the moisture content of your products to maintain quality and ensure optimum shelf-life. This robust and affordable moisture analyzer benefits from METTLERTOLEDO's extensive experience in manufacturing precision instruments and years of moisture analysis expertise.

The HE53 is simple to use, even for untrained operators. With on-screen assistance and our free Moisture Guide, you have everything you need to quickly setup and start making accurate moisture measurements. Designed in Switzerland, you will not only have confidence in your moisture results but also be reassured of great performance for many years to come.

Reliable Results



The HE53 delivers accurate and repeatable moisture measurements in just a few minutes.

- Reliable
- Efficient
- Increased productivity


Affordable Quality



Get excellent value for money with halogen drying technology and a high performance weighing unit.

- Modern technology
- Robustdesign
- Long instrument lifetime

Moisture Expertise



Benefit from our know-how with everything you need to start moisture analysis straight away.

- Quick set-up
- Freeonline training
- · Ready-to-use drying methods



Fast Moisture Results in an Easy 3-step Process

Moisture analysis has never been so easy, just follow the on-screen graphical guide and your results will be ready in just a few minutes.



1. Tare the empty weighing pan.



2. Add the sample and spread evenly.




3. Press start. See your results on-screen in just a few minutes.

METTLER TOLEDO Service

Ourworldwide service network is always on hand to support you with calibration and maintenance to keep your moisture analyzer performing at its peak.

HE53 Technical Data

Capacity	54 g
Readability	1 mg, 0.01% MC
Repeatability	0.15% (2 g sample), 0.05% (10 g sample)
Switch-off	Fully Automatic, Timed
Drying Programs	Standard, Rapid
Temperature Range	50 - 160°C (1°C increments)
Heating	Halogen
Result Display	%MC, %DC, %ATROMC, % ATRODC, g
Display	LCDback-lit
Display Functions	User Guidance, Progress Indicator
Weight	4.1 kg



Accessories



Aluminum sample pansSuitable for all applications to ensure best repeatability. Part No. 13865



Glass fiber filters Use with liquids and pastes to increase repeatability and reduce measurement time by up to 50%. Part No. 214464



Printers
The fastest way to document your moisture results.
Part No.
11124300 (RS-P25)
11124303 (RS-P26)

Free Moisture Guide



All you need to know about:

- Installation
- Operation
- Samples
- · Routine Testing

Polyscientific Enterprise Sdn Bhd

百利企业有限公司 152064-D

Melaka (HQ) 272, Taman Asean, Jalan Malim, 75250 Melaka

T +606 3350690 F +606 3351631

Shah Alam

14, Jalan Serendah 26/39, Kawasan Perindustrian HICOM, 40400 Shah Alam, Selangor

T +603 51036920 F +603 51036980

Penang

16, Jalan Sungai Tiram 7, 11900 Bayan Lepas, Penang

T +604 6371500 F +604 6371600

Johor 20-02, Jalan Permas 10/7, Bandar Baru Permas Jaya, 81750 Masai, Johor

T +607 2132694